






RN-100 | RWA-160, 200, 250, 320

COMPACT • MASSIVE CLAMP TORQUE

The compact, high speed RN-100 is especially suited for drilling and tapping machines. RWA-Series tables utilize a patent pending dual taper pneumatic clamping system which generates massive clamp torque - up to 300% greater than previous RN-Series rotary tables. RWA-Series tables feature a full range of options including rotary scales and hydraulic or pneumatic rotary joints.




Table Model		RN-100	RWA-160	RWA-200	RWA-250 (S)	RWA-320 (S)	
Versions available		R, L	R, L	R, L	R, L	R, L	
Spindle outer diameter	mm	80h7	100h7	120h7	140h7	180h7	
Table diameter (optional)	mm	(135)	(160, 200)	(200, 250)	250	320	
Center height	mm	110	135	160	160	210	
Center bore	Nose Diameter	mm	50H7	55H7	65H7	80H7	110H7
	Thru Diameter	mm	30	40	45	50	85
Table T-slot width (with face plate)		(10H8)	(12H8)	(12H8)	12H8	14H7	
Guide block width		14h7	14h7	18h7	18h7	18h7	
Servo motor (Fanuc)*		Alpha 2i	Alpha 2i	Alpha 4i	Alpha 8i (8is)	Alpha 8i (22is)	
Maximum motor speed	rpm	5,000	5,000	5,000	4,000 (4,000)	4,000 (3,000)	
Speed reduction ratio		1/36	1/72	1/72	1/90 (1/45)	1/120 (1/45)	
Maximum table speed	rpm	138.9	69.4	69.4	44.4 (88.8)	33.3 (66.6)	
Inertia converted into motor shaft x 10 ⁻³ kg-m ²		.23	.09	.17	.41 (.44)	.52 (1.66)	
Clamp system		Pneumatic	Pneumatic Dual Taper				
Clamp torque @72psi	Nm (ft. lbs.)	80 (59)	500 (369)	800 (590)	1,000 (737)	1,500 (1,106)	
Indexing accuracy		arc sec.	±22.5	±12.5	±10	±10	
Net Weight		kg (lbs.)	28 (62)	38 (84)	61 (134)	80 (176)	145 (319)
Allowable wheel torque		Nm (ft. lbs.)	176 (130)	206 (152)	288 (212)	596 (439)	939 (692)
Allowable work inertia		kg-m ²	.10	.64	1.25	1.95	4.48
Allowable work weight	 kg (lbs) [w/ tailstock]	25 (55) [50 (110)]	100 (220) [175 (385)]	125 (275) [250 (550)]	125 (275) [250 (550)]	175 (385) [375 (825)]	
	 kg (lbs)	50 (110)	200 (440)	250 (550)	250 (550)	350 (770)	
Allowable load when table clamped	 N (lbf)	5,880 (1,317)	10,800 (2,419)	14,400 (3,226)	14,400 (3,226)	24,800 (5,555)	
	 Nm (ft. lbs.)	80 (59)	500 (369)	800 (590)	1,000 (737)	1,500 (1,106)	
	 Nm (ft. lbs.)	156 (115)	780 (575)	1,900 (1,400)	1,900 (1,400)	4,700 (3,464)	

* Other motors & RPM available • Dimensions = mm
Specifications subject to change without notice

Dimensions

Drawings not to scale • Dimensions = mm


RN-100R



RN-100R



RWA-160R





RWA-160R


With optional rotary scale




RWA-200R



RWA-250R



RWA-320R



Options & Accessories

TPC NC Controller	
Chucks	
Tailstock	
Support Spindle	
Face Plate	
Encoder / Scale	
Pull Stud Device	
Rotary Joint	
PVC Cables	

The dimensions above are for tables with a FANUC servo motor. Other motors available (dimensions may increase).

Clamping Block and Bolt

Dimensions = mm

	Type	Q'ty	T-Slot Width	A	B	C	D	E	F	G	H	I	J	K	L	M
RN-100	-	2	14	-	-	-	-	-	-	-	17	8	55	-	23	12
RWA-160	-	2	14	-	-	-	-	-	-	-	17	8	60	-	23	12
RWA-200	-	2	18	-	-	-	-	-	-	-	21	11	65	-	28	16
RWA-250	I	4	18	25	12	80	12	33	35	22	21	11	65	40	28	16
RWA-320	I	4	18	30	15	90	16	31	43	25	21	11	70	46	28	16

Note 1: When using a machine with a T-slot pitch other than the above, use suitable clamping blocks and bolts that are available on the market, or order custom-made ones (opt).

Note 2: Clamping blocks are not included in RN-100, RWA-160 and RWA-200.

Type I

